

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

Having now described the preferred embodiment, the invention is claimed to be:

*Sub 27*  
*PI*  
1. A coin bank comprising:  
a coin hopper;  
a coin slide positioned below said coin hopper;  
and,

5 a coin separating and sorting assembly located between said coin hopper and said coin slide, said coin separating and sorting assembly comprising:

10 a separating wheel including at least one coin receiving aperture and a toroidal flange extending away from a face of said separating wheel, and

a wheel housing on which said separating wheel is supported, said wheel housing including a toroidal channel in which said toroidal flange of said separating wheel is accommodated.

2. The bank of claim 1 wherein said separating wheel toroidal flange comprises a set of gear teeth.

3. The bank of claim 2 further comprising a motor having an output shaft operably connected to said gear teeth of said toroidal flange for driving the separating wheel.

4. The bank of claim 3 further comprising a gear train positioned between said output shaft and said gear teeth of said toroidal shaft, one gear of said gear train being fastened on said output shaft and another gear of  
5 said gear train engaging said gear teeth of said toroidal flange.

5. The bank of claim 2 wherein said wheel housing toroidal channel includes an opening through which said gear teeth of said toroidal flange can be accessed.

05750320 020901

6. A coin bank comprising:

a coin hopper;  
a sorter coin container positioned below said coin hopper; and,

5 a coin separating and sorting assembly located between said coin hopper and said sorted coin container, said coin separating and sorting assembly comprising:

a separating wheel including at least one coin receiving aperture,

10 a wheel housing on which said separating wheel is supported, said wheel housing comprising:

a plurality of sorting apertures of different sizes, each aperture being sized to allow passage of a coin of a defined maximum diameter therethrough.

7. The bank of claim 6 wherein said wheel housing apertures are arranged in a size order.

8. The bank of claim 6 wherein at least one of said sorting apertures has a trailing edge with an angled surface.

9. The bank of claim 6 wherein said wheel housing further comprises a central portion located radially inwardly from said plurality of sorting apertures, said central portion having a recessed area in an upper surface thereof.

10. A coin bank comprising:  
a coin hopper;  
a sorted coin container positioned below said coin hopper; and,

5 a coin separating and sorting assembly located between said coin hopper and said coin slide, said coin separating and sorting assembly comprising:

a separating wheel including at least one

10 coin receiving aperture wherein said at least one coin  
receiving aperture in said separating wheel includes a  
curved leading edge having a radius of curvature only  
slightly larger than a diameter of a largest size coin  
meant to be sorted, and

15 a wheel housing on which said separating  
wheel is supported, said wheel housing including a  
plurality of sorting apertures of different sizes, each  
aperture being sized to allow passage of a coin of a  
defined maximum diameter therethrough.

11. The bank of claim 10 wherein said leading edge  
of each of said plurality of apertures of said separating  
wheel has a thickness slightly greater than a thickness  
of a thickest coin meant to be sorted.

12. The bank of claim 10 wherein each of said  
plurality of apertures in said separating wheel has a  
diameter which is smaller than a combined diameter of two  
of a smallest diameter ones of the coins meant to be  
5 sorted so that two of the smallest diameter ones of the  
coins meant to be sorted cannot fit into one aperture.

13. The bank of claim 10 wherein said at least one  
aperture in said separating wheel has a trailing edge  
with a tapered surface that is smaller in thickness than  
is a thickness of a thinnest one of the coins meant to be  
5 sorted in order to prevent two of the coins from becoming  
stacked in a single aperture.

14. A coin separating and sorting assembly  
comprising:

a separating wheel including at least one coin  
receiving aperture;

5 a wheel housing on which said separating wheel  
is supported, said wheel housing comprising at least one  
sorting aperture which is sized to allow passage of a



separating wheel and the wheel housing; and,

15

a coin rolling surface defined on one of the separating wheel and the wheel housing.

20. The assembly of claim 19 wherein said leading edge of each of said plurality of apertures of said separating wheel has a thickness slightly greater than a thickness of a thickest coin meant to be sorted.

21. The assembly of claim 19 wherein each of said plurality of apertures in said separating wheel has a diameter which is smaller than a combined diameter of two of a smallest diameter ones of the coins meant to be sorted so that the two of the smallest diameter ones of the coins meant to be sorted cannot fit into a single aperture.

5

22. The assembly of claim 19 wherein each of said plurality of apertures and said separating wheel has a trailing edge with a tapered surface that is smaller in thickness than is a thickness of a thinnest coin meant to be sorted in order to prevent two of the coins from becoming stacked in a single aperture.

5

23. A coin separating and sorting assembly comprising:

a separating wheel including at least one coin receiving aperture;

5

a wheel housing on which said separating wheel is supported, said wheel housing comprising at least one sorting aperture;

a coin support surface provided on one of the separating wheel and the wheel housing; and,

10

a coin rolling surface defined on one of the separating wheel and the wheel housing, wherein a trailing edge of the separating wheel at least one aperture is so shaped as to allow an associated coin held

15 in said at least one aperture to contact said coin  
rolling surface before the associated coin reaches the at  
least one sorting aperture.

5 24. The assembly of claim 23 wherein said trailing  
edge has a tapered surface that is smaller in thickness  
than is a thickness of a thinnest coin meant to be sorted  
in order to prevent two of the coins from becoming  
stacked in a single aperture.

25. The assembly of claim 24 wherein said wheel  
housing comprises a plurality of apertures arranged in  
order of increasing size.

26. The assembly of claim 25 wherein said plurality  
of apertures are spaced from each other.

27. A coin separating and sorting assembly  
comprising:

5 a separating wheel comprising:  
at least one coin receiving aperture  
located in a wall of said separating wheel,  
a surface adapted to contact a driving  
element to enable rotation of said separating wheel;  
a wheel housing on which said separating wheel  
is supported;  
10 a coin support surface provided on one of the  
separating wheel and the wheel housing for supporting a  
portion of an associated coin being moved by said  
separating wheel in relation to said wheel housing; and  
a coin rolling surface defined on one of said  
15 separating wheel and said wheel housing.

28. The assembly of claim 27 further comprising a  
motor operatively connected to said separating wheel  
surface to enable rotation of said separating wheel when  
said motor is actuated.

29. The assembly of claim 27 wherein each of said plurality of coin receiving apertures in said separating wheel includes a curved leading edge having a radius of curvature only slightly greater than a diameter of a largest size coin meant to be sorted.

30. The assembly of claim 29 wherein each of said plurality of coin receiving apertures in said separating wheel includes a trailing edge having a larger radius of curvature than said leading edge.

31. A coin separating and sorting assembly comprising:

a separating wheel comprising at least one coin receiving aperture located in said separating wheel, said at least one coin receiving aperture comprising a leading edge and a trailing edge, wherein said leading edge has a radius of curvature which is greater than is a radius of curvature of said trailing edge;

a wheel housing on which said separating wheel is supported;

a coin support surface provided on one of the separating wheel and the wheel housing for supporting a portion of an associated coin being moved by said separating wheel in relation to said wheel housing; and

a coin rolling surface defined on one of said separating wheel and said wheel housing.

32. A coin separating and sorting assembly comprising:

a separating wheel comprising at least one coin receiving aperture located in said separating wheel, said at least one aperture having a leading edge and a trailing edge, wherein at said leading edge, said separating wheel has a thickness slightly greater than a thickness of a thickest associated coin meant to be



10 sorted and wherein said trailing edge has a tapered  
surface that is smaller in thickness than is a thickness  
of a thinnest one of the associated coins meant to be  
sorted;

a wheel housing on which said separating wheel is  
supported;

15 a coin support surface provided on one of the  
separating wheel and the wheel housing for supporting a  
portion of an associated coin being moved by said  
separating wheel in relation to said wheel housing; and

20 a coin rolling surface defined on one of said  
separating wheel and said wheel housing.

33. A coin separating and sorting assembly  
comprising:

5 a separating wheel comprising at least one coin  
receiving aperture located in a wall of said separating  
wheel;

10 a wheel housing on which said separating wheel is  
supported, said wheel housing comprising at least one  
coin sorting aperture located therein, said wheel housing  
further comprising a central portion located radially  
inwardly of said at least one sorting aperture, said  
central portion having a recessed area in an upper  
surface thereof, wherein said recessed area is located  
adjacent said at least one coin sorting aperture of said  
wheel housing.